

# Uprites

## Uprites



### EXAMPLE PART NO.

**U 36**

**U** = Uprite  
**36** = Height: 36", 42", 48",  
 54", 60", 66", 72", 78",  
 84", 90", 96", 108", 120"

### STANDARD FINISH:

**PLT**

• Optional Tier I & II colors

### Uprite:

- Use for Wall & Island Sections
- Steel welded construction
- 3/16" thick face channel
- 1" slotted on center for maximum flexibility
- Includes side flanges to retain back material
- Includes leveling leg for uneven floors
- Includes top caps on Uprites 36" - 66"H
- **For pricing see section 100, pg 67**

**WARNING:** Unbalanced load capacity of the Extension Uprite is 2.500 in. - lbs., this is considerably less than the capacity of a standard Uprite. Do not exceed this unbalanced load. Overloading could cause the Uprite to tip over or collapse resulting in personal injury or property damage.



## Extension Uprite

### Extension Uprite:

- Factory installed connector to fit Lozier Uprites  
 See below for Extension Uprite End Trim
- **For pricing see section 100, pg 67**

### EXAMPLE PART NO.

**U 36 E**

**U** = Uprite  
**36** = Height: 6", 12", 18", 24", 30",  
 36", 42", 48"  
**E** = Extension

### STANDARD FINISH:

**PLT**

• Optional Tier I & II colors

## Uprite & Extension Uprite End Trim

### Uprite & Extension Uprite End Trim:

- One-piece trim (Two-piece if 108" & 120") snaps onto first & last Uprite or Extension Uprite
- Can be used on both sides of Extension Uprites where Extension Backs are not used
- **For pricing see section 100, pg 68**

### EXAMPLE PART NO.

**UET 36**

**UET** = Uprite End Trim  
**36** = Height: 6", 12", 18", 24",  
 30", 36", 42", 48", 54",  
 60", 66", 72", 78", 84",  
 90", 96", 108", 120"

### STANDARD FINISH:

**PLT**

• Optional Tier I & II colors

